




HDPE PIPES



**LIGHT WEIGHT, STRONG,
LONG LASTING AND MAINTENANCE FREE**



FLEXIBLE & SMALLER DIAMETER PIPES



CHEMICALLY INERT AND RESISTANT



OVERALL TOUGHNESS



LONGEVITY

EVERY INCH OF
VINYL UPVC IS VIRGIN
SO, EVERY DROP OF
WATER WILL BE PURE



**WE ARE
HERE TO
FIX YOUR
PROBLEMS**

HDPE PIPES & FITTINGS

Vinyl pipes are a safe, long lasting & cost effective solution for potable water supply, irrigation & bore well application. Vinyl HDPE Pipes are manufactured from virgin raw materials with the help of state of the art manufacturing facilities. Stringent tests on raw material & finished goods ensure the quality as per national & international standards. Vinyl strongly believes in providing quality products & services to all their valuable customers.

PRODUCT RANGE :

220mm to 250mm PE 63,80,100 grades as per IS:4984 in 2.5 to 16kgf/cm pressure class.

FITTINGS :

All the compatible fittings are made available in handmade form to cater all system requirements.

APPLICATIONS :

- Potable water mains, house connections & column pipes for submersible pumps
- Irrigation & agriculture, Sprinkler & drip irrigation
- Underground drainage & sewerage, coal handling in mines & Industrial applications

FEATURES AND BENEFITS :

- High impact resistant
- Resistant to low temperature
- Easy, quick & economical installation
- Long service life
- Excellent chemical & abrasion resistance
- Excellent UV & corrosion resistance
- Excellent water hammer resistance
- Ideal in shifting soil conditions & earthquake prone areas



Agriculture

Irrigation & agriculture, Sprinkler & drip irrigation



Water Distribution

Potable water mains, house connections, column pipes for submersible pumps



Underground Drainage

Underground drainage & sewerage, coal handling in mines. industrial applications

HDPE PIPES & FITTINGS

STANDARD DIMENSION RATIO (SDR) AND CORRESPONDING WALL THICKNESSES OF PIPES AS PER IS 4984:2016																				
SDR	SDR 41		SDR 33		SDR 26		SDR 21		SDR 17		SDR 13.6		SDR 11		SDR 9		SDR 7.4		SDR 6	
NOMINAL PRESSURE (PN) BAR																				
PE 63	PN 2		PN 2.5		PN 3.2		PN 4		PN 5		PN 6		PN 8		-		-		-	
PE 80	PN 2.5		PN 3.2		PN 4		PN 5		PN 6		PN 8		PN 10		PN 12.5		PN 16		PN 20	
PE 100	PN 3		PN 4		PN 5		PN 6		PN 8		PN 10		PN 12.5		PN 16		PN 20		-	
Nominal OD	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
16	-	-	-	-	-	-	-	-	-	-	-	-	-	-	1.8	2.1	2.2	2.5	2.7	3.1
20	-	-	-	-	-	-	-	-	-	-	-	-	1.9	2.2	2.3	2.6	2.7	3.1	3.4	3.8
25	-	-	-	-	-	-	-	-	-	-	1.9	2.2	2.3	2.6	2.8	3.2	3.4	3.8	4.2	4.7
32	-	-	-	-	-	-	-	-	1.9	2.2	2.4	2.7	2.9	3.3	3.6	4.1	4.4	4.9	5.4	6.0
40	-	-	-	-	-	-	1.9	2.2	2.4	2.7	3.0	3.4	3.7	4.2	4.5	5.1	5.4	6.0	6.7	7.5
50	-	-	-	-	2.0	2.3	2.4	2.7	3.0	3.4	3.7	4.2	4.6	5.2	5.6	6.3	6.8	7.6	8.4	9.3
63	-	-	-	-	2.5	2.9	3.0	3.4	3.7	4.2	4.7	5.3	5.8	6.5	7.0	7.8	8.6	9.6	10.5	117
75	1.9	2.2	2.3	2.6	2.9	3.3	3.6	4.1	4.5	5.1	5.6	6.3	6.9	7.7	8.4	9.3	10.2	11.3	12.5	13.9
90	2.2	2.5	2.8	3.2	3.5	4.0	4.3	4.8	5.3	5.9	6.7	7.5	8.2	9.1	10.0	111	12.2	13.5	15.0	16.6
110	2.7	3.1	3.4	3.8	4.3	4.8	5.9	6.6	6.5	7.3	8.1	9.0	10.0	111	12.3	13.6	14.9	16.5	18.4	20.3
125	3.1	3.5	3.8	4.3	4.8	5.4	6.0	6.7	7.4	8.2	9.2	10.2	11.4	12.7	13.9	15.4	16.9	18.7	20.9	23.1
140	3.5	4.0	4.3	4.8	5.4	6.0	6.7	7.5	8.3	9.2	10.3	11.4	12.8	14.2	15.6	17.3	19.0	21.0	23.4	25.8
160	3.9	4.4	4.9	5.5	6.2	6.9	7.7	8.6	9.5	10.6	11.8	13.1	14.6	16.2	17.8	19.7	21.7	24.0	26.7	29.5
180	4.4	4.9	5.5	6.2	7.0	7.8	8.6	9.6	10.6	11.8	13.3	14.7	16.4	18.1	20.0	22.1	24.4	26.9	30.0	33.1
200	4.9	5.5	6.1	6.8	7.7	8.6	9.6	10.7	11.8	13.1	14.7	16.3	18.2	20.1	22.3	24.6	27.1	29.9	33.4	36.8
225	5.5	6.2	6.9	7.7	8.7	9.7	10.8	12.0	13.1	14.7	16.6	18.4	20.5	22.7	25.0	27.6	30.5	33.7	37.5	41.4
250	6.1	6.8	7.6	8.5	9.7	10.8	12.0	13.3	14.7	16.3	18.4	20.3	22.8	25.2	27.8	30.7	33.8	37.3	41.7	46.0
280	6.9	7.7	8.5	9.5	10.8	12.0	13.4	14.8	16.5	18.3	20.6	22.8	25.5	28.2	31.2	34.4	37.9	41.8	46.7	51.5
315	7.7	8.6	9.6	10.7	12.2	13.5	15.0	16.6	18.6	20.6	23.2	25.6	28.7	31.7	35.0	38.6	42.6	47.0	52.5	57.9
355	8.7	9.7	10.8	12.0	13.7	15.2	16.9	18.7	20.9	23.1	26.1	28.8	32.3	35.6	39.5	43.6	48.0	52.9	59.2	65.2
400	9.8	10.9	12.2	13.5	15.4	17.0	19.1	21.1	23.6	26.1	29.5	32.6	36.4	40.1	44.5	49.1	54.1	59.6	66.7	73.5
450	110	12.2	13.7	15.2	17.3	19.1	21.5	23.8	26.5	29.3	33.1	36.5	40.9	45.1	50.0	55.1	60.9	67.1	75.0	82.6
500	12.2	13.5	15.2	16.8	19.3	21.3	23.9	26.4	29.5	32.6	36.8	40.6	45.5	50.2	55.6	61.3	67.6	74.5	83.4	91.8
560	13.7	15.2	17.0	18.8	21.6	23.9	26.7	29.5	33.0	36.4	41.2	45.4	50.9	56.1	62.3	68.6	75.7	83.4	93.4	102.8
630	15.4	17.0	19.1	21.1	24.3	26.8	30.0	33.1	37.1	40.9	46.4	51.1	57,3	63.1	70.0	77.1	85.2	93.8	105.0	115.6
710	17.3	19.1	21.6	23.9	27.3	30.1	33.9	37.4	41.8	46.1	52.2	57.5	64.6	71.2	78.9	86.9	96.0	105.7	118.4	130.3
800	19.5	21.6	24.3	26.8	30.8	34.0	38.1	42.0	47.1	51.9	58.9	64.9	72.8	80.2	88.9	97.9	108.2	119.1	-	-

*Pressure rating marked in red color are not covered under ISI mark

MDPE PIPES

Vinyl Medium Density Polyethylene pipe (MDPE) is light weight, flexible and durable piping system which is manufactured within the world class Quality Management Systems.

FEATURES AND BENEFITS :

- Light weight, Flexible and durable
- Crack resistant
- Robust construction with high impact strength
- Low friction losses due to excellent smooth internal surface
- Resistant to bacterial growth, corrosion, rusting etc.
- Excellent strength & stiffness
- Chemical resistance
- Suitable for cold and waste water distribution system

